

ARRANGEMENT AND METHOD FOR REMOVING HEAT
FROM A COMPONENT WHICH IS TO BE COOLED

CROSS REFERENCE

This application is a section 371 of PCT/EP2003/010729, filed 26 SEP. 2003, claiming priority from German application DE 102 42 382.9, filed 28 SEP. 2002, the contents of which are incorporated by reference.

FIELD OF THE INVENTION

The invention concerns an arrangement and a method for cooling a component.

BACKGROUND

Many components, in particular electrical components such as microprocessors, are becoming more and more powerful and, at the same time, are consuming more and more electrical power.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to make available a new arrangement and a new method for cooling a component.

This object is achieved, according to the present invention, by providing a coolant pump, associated with a fan driven by an electric motor, and magnetically coupling the fan rotor and the pump rotor together, so that no separate pump drive is needed. ~~the subject matter of Claim 1.~~ The magnetic coupling separates the pump region from the fan region in fluid-tight fashion. This ensures that the coolant is continuously available for cooling, and that the coolant does not leak out and cause damage. In addition, only one drive system is needed for the fan and the rotor, with a consequent reduction in parts, weight, and cost.

According to a further aspect of the invention, the object is also achieved by using a drive motor to impart a rotational motion to the fan rotor, using the magnetic coupling between the fan rotor and the pump rotor to cause the pump rotor to also rotate, and causing the coolant to flow as a result of the rotation of the pump rotor. ~~the method according to Claim 18.~~ Transfer of the rotary motion of the fan rotor to the pump rotor simplifies construction and decreases the number of parts required.

Further details and advantages of the invention are evident from the examples which are to be understood as a limitation of the invention, described below and depicted in the drawings. ~~independent claims.~~

Mark-up
Copy

BRIEF FIGURE DESCRIPTION

FIG. 1 is a perspective depiction of a preferred embodiment of a fluid cooling apparatus according to the present invention;

FIG. 2 is a side view of a heat absorber according to the present invention;

FIG. 3 is a section through the heat absorber, looking along line III-III of FIG. 2;

FIG. 4 is a plan view of the heat absorber, looking in the direction of arrow IV of FIG. 3;

FIG. 5 is a section through the heat absorber, looking along line V-V of FIG. 4;

FIG. 6 is a section through the heat absorber, looking along line VI-VI of FIG. 4;

FIG. 7 is a side view of the preferred embodiment of the fluid cooling apparatus according to the present invention shown in FIG. 1;

FIG. 8 is a section through the fluid cooling apparatus, looking along line VIII-VIII of FIG. 7;

FIG. 9 is an exploded view of a centrifugal pump used as an example in FIG. 1;

FIG. 10 is a plan view of a heat exchanger 28 as used in FIG. 1;

FIG. 11 shows a plate of a heat exchanger having a bent-out sheet-metal part;

FIG. 12 shows a plate of a heat exchanger having a preferred embodiment of a bent-out sheet-metal part;

FIG. 13 shows a temperature/rotation speed characteristic curve for determining the necessary rotation speed; and

FIG. 14 shows a fan having a fluid conduit for passage of a coolant.

DETAILED DESCRIPTION

FIG. 1 is a perspective depiction of a preferred embodiment of a fluid cooling apparatus 10 according to the present invention. Fluid cooling apparatus 10 preferably serves to cool an electronic component 12 (depicted only schematically), in particular a microcontroller (μ C), processor, or microprocessor (μ P).

Fluid cooling apparatus 10 comprises a heat absorber 20, a return hose line 22, a fluid pump 24, an interconnecting hose line 26, a heat exchanger 28, a fan 30, and a supply hose line 32. The flow directions are indicated by arrows 23 and 33.

Heat absorber 20 comprises an inlet 40 and an outlet 42, pump 24 an inlet 44 and an outlet 46, and heat exchanger 28 an inlet 48 and an outlet 50.

Outlet 42 of heat absorber 20 is connected via return hose line 22 to inlet 44 of pump 24. Outlet 46 of pump 24 is connected via interconnecting hose line 26 to inlet 48 of heat exchanger 28. Outlet 50 of heat exchanger 28 is connected via supply hose line 32 to inlet 40 of the heat absorber.

Heat absorber 20, return hose line 22, pump 24, interconnecting hose line 26, heat exchanger 28, and supply hose line 32 thus form a cooling circuit in which a coolant 52 can circulate. Coolant 52 can be a fluid, for example a glycol-water mixture (cooling fluid).

MANNER OF OPERATION OF FIG. 1

Coolant 52 flows through heat absorber 20; at inlet 40 the coolant has a temperature below the surface temperature of processor 12, in heat absorber 20 it absorbs heat from processor 12, and at outlet 42 it has a temperature that is less different from the surface temperature of processor 12 than at inlet 40.

Coolant 52 travels via line 22 to pump 24, which keeps the coolant circuit in motion and pumps it via line 26 to inlet 48 of heat exchanger 28.

Coolant 52 entering heat exchanger 28 has a higher temperature than the air flow, driven by fan 30, entering the air side of the heat exchanger. Heat is thereby transferred from coolant 52 to the air, and coolant 52 cools down.

Lastly, the cooled coolant is delivered through outlet 50 of heat exchanger 28 and line 32 to heat absorber 20 through the latter's inlet 40, in order to cool processor 12.

The arrangement of pump 24 upstream from the inlet of heat exchanger 28 is favorable because a slight heating of coolant 52 takes place during the pumping operation. Because of the greater temperature difference in heat exchanger 28, the latter works more effectively and achieves a greater cooling capacity than if pump 24 were located downstream from heat exchanger 28.

FIG. 2 is a side view of heat absorber 20.

FIG. 3 is a section through heat absorber 20, looking along line III-III of FIG. 2.

FIG. 4 is a plan view of heat absorber 20 from the side facing away from processor 12.

FIG. 5 is a section through heat absorber 20, looking along line V-V of FIG. 4.

FIG. 6 is a section through heat absorber 20, looking along line VI-VI of FIG. 4.

Heat absorber 20 comprises a heat absorption element 64 having a plurality of plates 66 and conduits 68 located between plates 66, an inlet-side part 60 having inlet 40, and an outlet-side part 62 having outlet 42.

An embodiment of heat absorption element 64 that is preferred in economic terms is manufactured by extrusion from a material having good thermal conductivity. The use of aluminum has proven

favorable, since it is inexpensive and offers weight advantages. The low weight greatly reduces the risk of damage to component 12 as a result of dynamic stress.

Inlet-side part 60 and outlet-side part 62 are connected in fluid-tight fashion to heat absorption element 64.

Coolant 52 travels through inlet 40 into inlet-side part 60, and from there via conduits 68 of heat absorption element 64 to outlet-side part 62, which it leaves through outlet 42.

As it flows through conduits 68, the coolant absorbs heat that was transferred from upper side 13 of processor 12 to side 70 of heat absorption element 64 facing toward the processor, and thus also to plates 66.

A heat transfer improvement medium, in particular a thermally conductive film and/or a thermally conductive paste, is preferably arranged between heat absorber 20 and component 12 that is to be cooled. Better heat transfer is thereby obtained.

FIG. 7 is a side view of the preferred embodiment of fluid cooling apparatus 10 according to the present invention shown in FIG. 1.

FIG. 8 is a schematic section through a preferred embodiment of fluid cooling apparatus 10.

Fan 30 comprises a fan housing 71, a stator 76 mounted on the latter via a plurality of spokes 74, and a rotor 78 having fan blades.

Pump 24 comprises a magnet cup 80 connected to rotor 78 of fan 30, a pump housing 82 having a bearing journal 83, and a pump wheel 84 having pump vanes 86.

Pump housing 82 is connected to fan housing 71 via a retaining spider 72.

Heat exchanger 28 is connected to fan 30 on the opposite side from pump 24.

Pump 24 is driven by rotor 78 of fan 30 via a magnetic coupling. For that purpose, magnet cup 80 is immovably connected to rotor 78. Pump housing 82 is retained by retaining spider 72 so that it cannot rotate along with magnet cup 80. Pump wheel 84 is likewise magnetic, and is bearing-mounted in pump housing 82 rotatably via bearing journal 83. Magnet cup 80 is also bearing-mounted via pump housing 82. When magnet cup 80 is rotated by motor 76 of fan 30, pump wheel 84 is therefore also moved, and as a result pump vanes 86 are driven. This causes pumping of coolant 52 on the principle of a centrifugal pump.

Because of the coupling of fan 30 and pump 24, direct regulation of the temperature of component 12 can be accomplished.

Lower-noise operation is thus possible if there is less load on processor 12.

The cooling apparatus preferably comprises a rotation speed controller n-RGL 122 for regulating the rotation speed of fan 30. The target rotation speed for the rotation speed controller is preferably determined as a function of a temperature value, that temperature value being ascertained by a temperature sensor 120 mounted on component 12 that is to be cooled.

As alternatives to plastic-on-plastic journal mounting of pump wheel 84 in pump housing 82, mounting by way of a rolling bearing or also a radial bearing configuration is possible.

FIG. 9 is an exploded view of centrifugal pump 24 that is used by way of example.

Pump housing 82 comprises a first housing part 82' and a second housing part 82". Inlet 44 and outlet 46 are arranged in first housing part 82', and bearing journal 83 in second housing part 82". First housing part 82' and second housing part 82" are produced from a suitable plastic, for example by injection-molding. Connection of the two housing parts is effected, for example, by ultrasonic welding.

Pump wheel 84 comprises pump vanes 86 at its end toward the first housing, and is fabricated from a suitable plastic, for example by injection-molding. Magnet particles or segments, for example hard ferrite powders, are embedded in the plastic, and after injection-molding the desired magnetization is imposed, as indicated in FIG. 9 by N (north pole) and S (south pole). As a result, in addition to its property as a fluid flow generator, pump wheel 84 also has the capability of transferring the magnetic torque generated by magnet cup 80, without a stuffing box, to pump wheel 84.

Magnet cup 80 is manufactured as a deep drawn steel part or steel cup having a magnet ring, or preferably, in the same manner as pump wheel 84, from an injection-moldable plastic having embedded magnetic particles or segments, and the desired magnetization is then imposed as also shown in FIG. 9.

Upon assembly, pump wheel 84 is inserted into second housing part 82", first housing part 82' is pushed on, and the two housing parts 82', 82" are joined in fluid-tight fashion. Pump housing 82 is then moved into magnet bell 80.

What results is a pump 24 with a very low parts count which can be produced inexpensively. With the magnetic coupling, furthermore, it is much easier than with a continuous shaft to achieve freedom from leaks, which is a necessity for use in the

interior of a computing system.

Pump wheel 84 and/or magnet cup 80 can alternatively be made not from a plastic having embedded magnet particles but instead, for example, from pressed magnets or pressed magnets injection-embedded in plastic.

FIG. 10 is a plan view of a preferred embodiment of heat exchanger 28.

Heat exchanger 28 comprises a housing 88 having an inlet-side part 88 with inlet 48, an outlet-side part 92 with outlet 50, a plurality of conduits 94 that extend between inlet-side part 88 and outlet-side part 92, and a plurality of plate regions 96 extending between conduits 94.

Coolant 72 travels through inlet 48 into inlet-side part 90 of heat exchanger 28; from there it travels through conduits 94 into outlet-side part 92, whence it leaves the heat exchanger through outlet 50.

The air set in motion by fan 30 flows through plate regions 96 that serve to increase the heat-exchange area. For that purpose, the heat exchanger is arranged in the air flow region of fan 30 (see FIG. 8).

The heat transferred from coolant 52 to the air ensures cooling of coolant 52.

Fluid cooling apparatus 10 preferably has further connectors (not depicted) through which lines from further heat absorbers 20 can be connected. They are preferably completely preassembled and filled so that, for example, installation in the computer housing can be performed without difficulty. Fan 30 thus simultaneously ventilates other components in the computer housing, e.g. graphics cards, chipset modules, and hard drives. Overall cooling of the system is thereby improved.

The flow direction of the air preferably proceeds from the heat exchanger outflow side, i.e. the side at which air emerges, directly out of the housing, e.g. out of a computing system. Other components located in the housing are thereby cooled more effectively, which increases the service life of the computing system and/or allows less air flow. This minimizes noise.

Ventilation slots are preferably located in the housing on the side opposite the heat exchanger, so that the components located in the housing are continuously cooled in the resulting air flow. The heat exchanger functions simultaneously as a noise suppressor for the air flowing out of the housing.

Fluid cooling apparatus 10 requires very little space and has very little mass in the vicinity of component 12 to be cooled.

The magnetic coupling of fan 30 and pump 24 reduces the space requirement, parts count, and therefore manufacturing costs. There is moreover no need for an additional electrical connector for pump 24.

Electric motor 76, for example an electronically commutated external- or internal-rotor motor, can preferably be regulated in terms of its rotation speed, for example as a function of the temperature of component 12 to be cooled (see FIG. 7). As a result, the cooling capacity or rotation speed can be kept as low as is necessary, and needs to be increased only if the ambient temperature and/or computing power is correspondingly high. The noise generated is thus likewise diminished; this is very advantageous, for example, in the context of a computing system in an office..

The heat absorber and heat exchanger are preferably implemented using flat-tube technology. An extremely compact configuration, maximum power density, and decreased weight can thereby be achieved. This is very advantageous when the heat absorber is placed directly on a processor to be cooled in a computer, since processors have little capacity for mechanical stress and the available heat transfer area is very small.

Deep drawn parts are preferred for inlets and outlets 60, 62, 90, 92.

Plates 96 are preferably used in order to improve the efficiency of the flat tubes.

The flat tubes are preferably extruded parts.

It is advantageous in terms of heat transfer that the base surface of the heat absorber is flat and exhibits little surface roughness.

All the aforementioned elements can be manufactured and assembled very economically, so that the product as a whole can be manufactured inexpensively.

A radial fan is preferably selected as the fan, in which context the heat exchanger can preferably be arranged around the enveloping surface of the radial fan. Mounting the heat exchanger around the enveloping surface of the radial fan increases the heat exchanger area and therefore the cooling capacity. The heat exchanger comprises, for example, fluid conduits that extend on the enveloping surface from one end face of the radial fan to the opposite end face.

FIG. 11 shows a portion of a plate 96 of heat exchanger 28 having a bent-out sheet-metal part 130 that is referred to as a "shutter." Bent-out sheet-metal part 130 is produced by stamping out three sides 131', 131", and 131'" forming a "U," and then bending

out sheet-metal part 130 defined by the three sides 131', 131", and 131'''. Application of a plurality of such bent-out sheet-metal parts 130 to plates 96 results, for example, in an 80% improvement in the cooling capacity of the heat exchanger. Open end 132 of bent-out sheet-metal part 130 preferably faces the opposite way from direction 134 of the air flow through heat exchanger 28.

FIG. 12 shows a portion of a plate 96 of heat exchanger 28 having a further embodiment of a bent-out sheet-metal part 135. The latter is produced by making a cut 136 into plate 96, followed by deep-drawing and bending out. The bending-out operation creates an opening 138 through which air can flow. Open side 137 of the bent-out sheet-metal part is preferably oriented oppositely to direction 139 of the air flow.

FIG. 13 shows a preferred exemplifying embodiment of a temperature/rotation speed characteristic curve 150 that indicates rotation speed n of fan 30 of liquid cooling system 10, and thus also the rotation speed of pump 24. This temperature/rotation speed characteristic curve 150 is preferably used in conjunction with a measurement of the temperature of coolant 52. For that purpose, sensor 120 (see FIG. 7) is preferably positioned in the vicinity of microprocessor 12 at a point in the coolant circuit at which the coolant has already absorbed the heat of microprocessor 12.

The rotation speed of fan 30 is controlled in open- or, preferably, closed-loop fashion as a function of rotation speed value n resulting from temperature/rotation speed characteristic curve 150.

According to the temperature/rotation speed characteristic curve, up to a first temperature T_1 (e.g. 30 degrees C) a minimum rotation speed n_1 is defined at which fan 30 works very quietly. The result is that a minimum cooling level is continuously maintained, as experience has indicated is necessary. If temperature T in the coolant rises to $T > T_1$, rotation speed n of fan 30 is then increased until at a temperature T_2 (e.g. 70 degrees C), maximum rotation speed n_2 of fan 30 is reached. At this operating point the flow velocities in both the closed-circuit fluid flow and the open-circuit fan flow are maximal, and maximum heat transfer is established. The maximum heat load is therefore also being dissipated. The dependence of rotation speed n on temperature T is shown as being linear, but in other instances can have a different, e.g. exponential, character.

In the case of components to be cooled that have an internal temperature sensor, in particular microprocessors, the sensor's temperature information can also be utilized to determine rotation

speed n . The temperature information is picked off for this purpose, for example, at a suitable location on the main circuit board.

FIG. 14 shows a preferred exemplifying embodiment of a fan 30 for use in a fluid cooling apparatus 10. Only fan 30 is depicted, without pump 24.

Fan housing 71 of fan 30 comprises a fluid conduit 100 through which a coolant 52 can be conveyed. Fluid conduit 100 comprises an inlet 102 and an outlet 104. Coolant can flow into fan housing 71 through inlet 102, and flow out through outlet 104.

Because coolant 52 is being pumped through fan housing 71, on the one hand a further cooling of coolant 52 takes place (i.e. the fan also acts as a heat exchanger), and on the other hand fan 30 is effectively protected from overheating. For this purpose, fluid conduit 100 is preferably additionally routed past the electrical components of stator 76. The fan preferably comprises further fluid conduits in addition to fluid conduit 100.

For better heat transfer, the fan housing preferably comprises cooling fins that are arranged on the surface of fan 30 and/or project into fluid conduit 100.

Fan housing 71 is preferably made from a thermally conductive plastic. This enables better heat transfer between coolant 52 and the fan housing surface at which heat dissipation takes place.

In a preferred embodiment of the invention, pump 24 is removable from fan 30 (FIG. 8), i.e. pump 24 and fan 30 are connected detachably. This is achieved, for example, by way of a screw connection or quick-release coupling between pump 24 and fan 30. Pump retaining member 72, in particular, is detachable from pump 24 and/or from fan 30 for this purpose. This embodiment has the advantage that fan 30 can be replaced independently of the coolant circuit. It is thus unnecessary to drain the coolant when replacing fan 30.

Heat absorber 20 (FIG. 2 and FIG. 3) preferably comprises, on its outer side, cooling fins (not depicted) with which additional cooling of coolant 52 flowing through heat absorber 20 is achieved. It is also preferred if heat absorber 20 comprises on its outer side an additional fan (not depicted) with which additional cooling of coolant 52 flowing through heat exchanger 20 can likewise be achieved.

Coolant lines 22, 26, 28 are preferably constituted by metal hoses, since the latter exhibit good aging resistance, fluid-tightness, and heat dissipation. Bendable corrugated tubes are also preferably used.

CLAIMS

1. (Currently Amended) An arrangement (10) for cooling a component, ~~in particular an electronic component,~~ which arrangement comprises:
a pump (24) for pumping a coolant (52), which pump (24) comprises a pump rotor (84);
a fan (30) that comprises a fan rotor (78) associated with which is an electric motor (76) to drive it,
the pump rotor (84) and the fan rotor (78) being separated from one another in fluid-tight fashion and drivingly connected to one another via a magnetic coupling (80, 84).

2. (Currently amended) The arrangement according to claim 1, wherein
the magnetic coupling (80, 84) ~~comprises~~ comprising a magnet cup (80) that is connected to the fan rotor (78),
the pump rotor (84) being made at least partly of a magnetic material; and
the magnet cup (80) being arranged relative to the pump rotor (84) in such a way that a rotation of the magnet cup (80) causes, via the magnetic coupling, a rotation of the pump rotor (84).

3. (Currently Amended) The arrangement according to claim 2, wherein the pump rotor (84) ~~being produced from a material, in particular plastic, in which material are embedded~~ comprises a mass of non-magnetic material and a plurality of magnetized magnet particles or segments embedded in said non-magnetic material.

4. (Currently Amended) The arrangement according to claim 1 ~~any of the preceding claims,~~
the pump rotor (84) comprising a plurality of pump vanes (86) for generating a flow of the coolant (52).

5. (Original) The arrangement according to claim 4,
the pump vanes (86) being implemented integrally with the pump rotor (84).

6. (Currently Amended) The arrangement according to claim 1,
~~any of the preceding claims~~,

the fan (30) comprising a fan housing (71) and the pump (24)
comprising a pump housing (82); and

having a pump retaining member (72) that connects the fan
housing (71) to the pump housing (82).

7. (Currently Amended) The arrangement according to claim 6,
wherein the fan housing (71) and the pump retaining member (72) are
~~being~~ implemented integrally.

8. (Currently Amended) The arrangement according to claim 1,
~~any of the preceding claims~~,

which comprises a heat exchanger (28) for cooling the coolant
(52), which exchanger is located in an air flow region of the fan
(30) and is in fluid communication with the pump (24) for the
coolant (52).

9. (Currently Amended) The arrangement according to claim 8,
wherein the heat exchanger (28) ~~being~~ is implemented as a flat-tube
heat exchanger.

10. (Currently Amended) The arrangement according to claim 8,
~~or 9~~,

the heat exchanger (28) comprising a plurality of plates (96)
for the passage of air.

11. (Original) The arrangement according to claim 10,
the plates (96) comprising a plurality of shutters (130, 135)
for improving the absorption of heat by the air passing through.

12. (Currently Amended) The arrangement according to claim 8,
~~any of claims 8 through 11~~,

the heat exchanger (28) comprising a heat exchanger housing
(88) and the fan (30) comprising a fan housing (71); and

the heat exchanger housing (88) and fan housing (71) being
implemented integrally.

13. (Currently Amended) The arrangement according to claim
12,

~~which comprises~~ further comprising a pump retaining member
(72) that connects the fan housing (71) to the pump (24),

the heat exchanger housing (88), the fan housing (71), and the
pump retaining member (72) being implemented integrally.

14. (Currently Amended) The arrangement according to claim 8,
~~any of the preceding claims~~,

which comprises a heat absorber (20) for cooling a component,
which heat absorber (20) is in fluid communication both with
the pump (24) and with the heat exchanger (28) and forms with them a
coolant circuit.

15. (Original) The arrangement according to claim 14,
the heat absorber (20) being implemented as a flat-tube heat
absorber.

16. (Currently Amended) The arrangement according to
claim 15,

the heat absorber (20) comprising a heat absorption element
(64) that is manufactured from a material selected from the group
consisting of copper or and aluminum.

17. (Currently Amended) The arrangement according to
claim 14, ~~any of claims 14 through 16~~,

the heat absorber (20) comprising external cooling fins.

18. (Currently Amended) The arrangement according to
claim 14, ~~any of claims 14 through 17~~,

an additional fan being associated with the heat absorber (20)
for cooling.

19. (Currently Amended) The arrangement according to claim 14, ~~any of claims 14 through 18~~, comprising a component (12) to be cooled,

a heat transfer improvement medium, ~~in particular a thermally conductive foil and/or a thermally conductive paste~~, being arranged between the heat absorber (20) and the component (12) to be cooled.

20. (Currently Amended) The arrangement according to ~~any of the preceding claims~~, claim 1, further comprising a rotation speed controller (122) ~~being~~ associated with the electric motor (76).

21. (Currently Amended) The arrangement according to claim 20, ~~which comprises~~ further comprising a temperature sensor (120) that is connected to the rotation speed controller (122) in order to control a temperature-dependent rotation speed.

22. (Currently Amended) The arrangement according to claim 21, wherein the temperature sensor (120) ~~being an~~ is a Negative Temperature Coefficient (NTC) resistor.

23. (Currently Amended) The arrangement according to claim 21 ~~or 22~~, wherein the temperature sensor (120) ~~being arranged in the region of~~ is located adjacent the heat absorber (20).

24. (Currently Amended) The arrangement according to claim 21, ~~any of claims 21 through 23~~, wherein the temperature sensor (120) ~~being~~ is arranged adjacent ~~in the region of~~ a component (12) to be cooled.

25. (Currently Amended) The arrangement according to claim 21, ~~any of claims 21 through 24~~, wherein the temperature sensor (120) ~~being~~ is arranged at least partly in the coolant in thermally conductive relation to a circuit of said coolant.

26. (Currently Amended) The arrangement according to claim 1, ~~any of the preceding claims~~, wherein the fan (30) ~~being~~ is implemented as a radial fan.

27. (Currently Amended) The arrangement according to claim 1, any of the preceding claims, wherein the fan (30) and the pump (24) ~~being~~ are connected detachably to one another.

28. (Currently Amended) The arrangement according to claim 27, the fan (30) and the pump (24) being connected to one another via ~~a screw connection and/or~~ a quick-release coupling.

29. (Currently Amended) The arrangement according to claim 1, any of the preceding claims, further comprising metal conduits ~~metal hoses and/or metal tubes being provided for fluid communication~~ circulation of said coolant.

30. (Currently Amended) The arrangement according to claim 1, any of the preceding claims, wherein the fan (30) ~~comprising~~ is formed with a fluid conduit (100) for conveying a coolant (52) therethrough.

31. (Original) The arrangement according to claim 30, wherein the fan (30) comprises a fan housing (71), and the fluid conduit (100) is implemented in the fan housing (71).

32. (Original) The arrangement according to claim 31, wherein the fan housing (71) comprises cooling fins.

33. (Currently Amended) The arrangement according to claim ~~31, or 32,~~ wherein the fan housing (71) ~~is implemented from~~ comprises a thermally conductive plastic.

34. (Currently Amended) The arrangement according to claim 30, any of claims 30 through 33, wherein the fan (30) comprises a stator (76) having electrical components, the fluid conduit (100) being routed past the electrical components of the stator (76) for cooling.

35. (Original) A method for cooling a component,
using a fan (30) that comprises a fan rotor (78) and a drive
motor (76),
using a pump (24) that comprises a pump rotor (84),
using a coolant (52) that is pumpable by means of the pump
(24),
using a magnetic coupling (80, 84) that drivingly connects the
fan rotor (78) and the pump rotor (84),
comprising the following steps:
A) the fan rotor (78) has a rotational motion imparted to it
by means of the drive motor (76);
B) the pump rotor (84) has a rotational motion imparted to it,
via the magnetic coupling (80, 84), by means of the rotational
motion of the fan rotor (78);
C) the coolant (52) is caused to flow by the rotational motion
of the pump (84).

36. (Original) The method according to claim 35,
using a heat exchanger (28) to cool the coolant, which
exchanger is in fluid communication with the pump (24),
which method additionally comprises the following steps:
A2) air is caused to flow by the rotational motion of the fan
rotor (78);
C2) the coolant (52) is pumped through the heat exchanger (28)
by the pump (24);
C3) the coolant is cooled by the flow of heat from the coolant
(52) to the air that has been caused to flow.

37. (Original) The method according to claim 36,
using a heat absorber (20) to cool a component, which
exchanger is in fluid communication with the pump (24) and the heat
exchanger (28),
which method additionally comprises the following step:
C4) the coolant (52) is pumped through the heat absorber (20)
by the pump (24).

38. (Original) The method according to claim 37,
the pump (24), the heat exchanger (28), and heat absorber (20)
forming a coolant circuit,

which method additionally comprises the following step:

C5) the coolant is pumped through the coolant circuit in the
sequence: pump (24), heat exchanger (28), heat absorber (20), pump
(24).

39. (Original) The method according to claim 38,
the pump (24), the heat exchanger (28), and the heat absorber
(20) forming a coolant circuit,

which method additionally comprises the following step:

C6) the coolant (52) is pumped through the coolant circuit in
the sequence: pump (24), heat absorber (20), heat exchanger (28),
pump (24).

40. (Currently amended) The method according to claim 36,
~~any of claims 36 through 39,~~

using a housing, ~~in particular a computer housing,~~ in which
the heat exchanger is located,

which method additionally comprises the following step:

A3) the air heated by the heat exchanger (28) is discharged
directly from the housing.

41. (Currently Amended) The method according to claim 40,
~~which method additionally comprises~~ further comprising the
following step of:

A4) directing the air flowing into the housing, as a result of
the rotational motion of the fan rotor (78), ~~is directed~~ over
further components located in the housing,
~~, in particular graphics cards, chip sets, hard drives, and power
supplies.~~

42. (Currently Amended) The method according to claim 35,
~~any of claims 35 through 41,~~
~~the drive motor (76) comprising a rotation speed controller,~~
~~using a temperature sensor that generates a sensor signal,~~
~~which method additionally comprises the following steps:~~
~~A5) the sensor signal is allocated to a target rotation speed~~
~~value,~~
~~A6) the rotation speed of the drive motor (76) is regulated to~~
~~the target rotation speed value by the rotation speed controller.~~
further comprising the steps of:
sensing temperature in a temperature sensor (120) and
generating a corresponding temperature output value;
associating said temperature output value, in a rotational
speed controller (122), with a corresponding target rotation speed,
and
driving said motor (76) toward said target rotation speed, in
accordance with control signals applied by said speed controller to
said motor.

ABSTRACT

~~The invention concerns an~~ An arrangement, for heat dissipation from a component that is to be cooled, ~~which arrangement comprises features:~~ a pump for pumping a coolant, which pump comprises a pump rotor; a fan that comprises a fan rotor associated with which is an electric motor to drive it, the pump rotor and the fan rotor being separated from one another in fluid-tight fashion and drivingly connected to one another via a magnetic coupling. It also relates to a method for heat dissipation from a component that is to be cooled, using a fan that comprises a fan rotor and a drive motor, using a pump that comprises a pump rotor, using a coolant that is pumpable by means of the pump, comprising the following steps:

A) the fan rotor has a rotational motion imparted to it by means of the drive motor; B) the pump rotor has a rotational motion imparted to it, via the magnetic coupling, by means of the rotational motion of the fan rotor; C) the coolant is caused to flow by the rotational motion of the pump.